

PROPOSAL FOR EXPERIMENT AT RCNP

1 January 2000

TITLE:

Measurements of Intermediate Energy Neutron Transport through Materials

SPOKESPERSON:

Kazuo Shin
 Department of Nuclear Engineering, Kyoto University
 Associate Professor
 Yoshida, Sakyo-ku, Kyoto 606-8501
 Phone number +81-75-753-5825
 FAX number +81-75-753-5845
 E-mail shin@nucleng.kyoto-u.ac.jp

EXPERIMENTAL GROUP:

Kazuo Shin	Department of Nuclear Engineering, Kyoto Univ.	Assoc. Professor
Tatsuhiko Sato	Department of Nuclear Engineering Kyoto Univ.	D3
Taku Itoh	Department of Nuclear Engineering, Kyoto Univ.	M1
Takahiro Moriya	Department of Nuclear Engineering, Kyoto Univ.	B4
Shingo Taniguti	Beam line division, Japan Synchrotron Research Institute	Researcher

RUNNING TIME: Installation time without beam 1 days(for each beam time)
 Development of device 1 days
 Data runs 3 days

BEAM LINE:

Ring : N0 course

BEAM REQUIREMENTS:

Type of particle	p
Beam energy	150 MeV
Beam intensity	≤ 500 nA
Any other requirements	energy resolution \leq halo-free, small emittance

BUDGET:

Experimental expenses	0 yen
-----------------------	-------

TITLE:

Title title Measurements of Intermediate Energy Neutron Transport through Materials

SPOKESPERSON: Kazuo Shin

SUMMARY OF THE PROPOSAL

To obtain standard data of neutron attenuation rate in shield materials and to understand the reliability of simulation calculation methodology for monoenergetic neutrons, neutron spectra just behind shield materials are measured by unfolding method, using a 10 in. by 10 in. NE-213 as the detector. Attenuation rate of peak neutrons is also measured by TOF method. As the first trial of the experiment, iron shields up to 60 cm and 150 MeV monoenergetic neutrons are used. The minimum requirement of the beam time is 3 days.