

## PROPOSAL FOR EXPERIMENT AT RCNP

22 July 2003

**TITLE:**

Measurements of neutron energy spectra from thick target bombarded by high energy protons

**SPOKESPERSON:**

Full Name Noriaki NAKAO  
 Institution Radiation Science Center,  
 High Energy Accelerator Research Organization (KEK)  
 Title or Position Research Associate  
 Address 1-1 Oho, Tsukuba, Ibaraki 305-0801, JAPAN  
 Phone number +81-29-879-6004  
 FAX number +81-29-864-4051  
 E-mail noriaki.nakao@kek.jp

**EXPERIMENTAL GROUP:**

Full Name	Institution	Title or Position
Noriaki NAKAO	High Energy Accelerator Research Org. (KEK)	(Research Associate)
Shingo TANIGUCHI	Japan Synchrotron Radiation Res. Inst.(JASRI)	(Researcher)
Takashi NAKAMURA	Cyclotron RI Center (CYRIC), Tohoku Univ.	(Professor Emeritus)
Koji OISHI	Institute of Technology, Shimizu Corporation	(Senior Research Engineer)
Hiroshi YAMAKAWA	Institute of Technology, Shimizu Corporation	(Research Engineer)
Yoshitomo UWAMINO	Institute of Physical and Chemical Res.(RIKEN)	(Manager, Safety Center)
Mamoru BABA	Cyclotron RI Center (CYRIC), Tohoku Univ.	(P)
Kichiji HATANAKA	RCNP, Osaka Univ.	(P)
Takane SAITO	RCNP, Osaka Univ.	(AP)
Atsushi TAMII	RCNP, Osaka Univ.	(AP)

**RUNNING TIME:** Installation time without beam 1 days (for each beam time)  
 Development of device 1.5 days  
 Data runs 6 days

**BEAM LINE:** Ring : N0 course

**BEAM REQUIREMENTS:** Type of particle p  
 Beam energy 150, 250, 400 MeV  
 Beam intensity  $\leq 10$  nA  
 Any other requirements halo-free, small  
 emittance, 1/9 beam pulsing

**BUDGET:** Traveling expenses 600,000 yen

**TITLE:**

**Measurements of neutron energy spectra from thick target bombarded by high energy protons**

**SPOKESPERSON:** Noriaki NAKAO

**SUMMARY OF THE PROPOSAL**

The energy and angular distributions of neutrons produced from thick targets (thick target yields, TTY) will be measured using various kinds of materials and proton energies. The neutron energy spectra will be measured by using the time-of-flight (TOF) method, and production angles in a few forward directions will be selected by moving the target in the beam swinger magnet. Detector efficiencies will be also measured by using the  $p\text{-}^7\text{Li}$  quasi-monoenergetic neutrons to obtain the accurate neutron energy spectra. These data are useful to estimate the neutron generation by the beam loss at the beam line materials in the proton accelerator facilities for radiation protection and shielding purposes. It will take 2.5 days to measure the TTY for 4 targets and 3 angles and detector efficiency. Total requirement of the beam time is 7.5 days for 3 proton energies.