



## Present Status of Reactor Neutrino Experiments

## Guofu Cao

(on behalf of JUNO collaboration) Institute of High Energy Physics DBD16, Osaka, Japan November 8th – 10th, 2016



### Very short baseline O(1m~10m) experiments will not be covered in this talk.

## ✤ A brief summary on short baseline (~1 to 2km) reactor neutrino experiments ➢ Daya Bay, Double Chooz, RENO

- Focus on medium baseline (~50km) reactor neutrino experiments
  - > JUNO
  - ≻ RENO-50

#### Reactor v: one of ways to understand v nature

- **\* KamLAND**+Solar provide the best measurement for  $\theta_{12}$  and  $\Delta m_{21}^2$ .
- In 2012, the last unknown mixing angle θ<sub>13</sub> was determined to be surprisingly large ~ 9° by the Daya Bay, as well as RENO and Double Chooz.
- Determining Mass Hierarchy & precision measurement of θ<sub>12</sub>,
   Δm<sup>2</sup><sub>21</sub> and Δm<sup>2</sup><sub>31</sub>
   > JUNO
  - ➢ RENO-50



## Keys in $\theta_{13}$ measurements

- □ Powerful reactor complexes and large target mass → large statistics.
   □ Near-Far identically designed detectors → reactor flux uncertainty cancellation.
   □ Underground → reduce backgrounds from cosmic rays.
- □ Gd-doped liquid scintillator → powerful radioactivity background rejection.







#### Antineutrinos are detected via the Inverse Beta Decay (IBD) reaction



Gd-doped liquid scintillator
 nGd + nH: Daya Bay, RENO, Double
 Chooz
 Liquid scintillator
 nH: JUNO, RENO-50



## Results of $\theta_{13}$ and $\Delta m_{ee}^2$



 $sin^{2}2\theta_{13}$ =(11.1  $\pm$  1.8(stat.+syst.))  $\times$  10<sup>-2</sup>

Moriond 2016

#### Daya Bay experiment

> Is expected to continuously run until 2020.

The uncertainties of sin<sup>2</sup>2θ<sub>13</sub> and |Δm<sup>2</sup><sub>ee</sub>|, from ~4% to ≤ 3%.
□ RENO

- Expected to take total 5 years of data.
- > The uncertainties of  $\sin^2 2\theta_{13}$  and  $|\Delta m^2_{ee}|$ , from ~12% to  $\leq 5\%$ .
- Double Chooz
  - 3 years near/far detector running.
  - ➤ The uncertainties of sin<sup>2</sup>2θ<sub>13</sub>, from ~16% to ≤ 10%.

The uncertainties can be further improved by combining Daya Bay, RENO and Double Chooz.



## Reactor flux anomaly



### Reactor flux spectrum distortion





- All 3 experiments observed excess events in 4-6 MeV region.
- Excess events are correlated with reactor power.
- Excess does not appear in <sup>12</sup>B spectra.

#### Determine MH with Reactors



# JUNO has been approved in Feb. 2013. ~ 300 M\$. JUNO is a multi-purpose reactor neutrino experiment.

- 20 kton LS detector
- ➤ 3%/sqrt(E) energy resolution
- > 700 m overburden
- > Rich physics
  - Reactor neutrino for MH and precision measurement of oscillation parameters
  - ✓ Supernovae neutrino
  - ✓ Geo-neutrino
  - ✓ Solar neutrino
  - ✓ Atmospheric neutrino
  - ✓ Exotic searching, such as proton decay, dark matter

### JUNO Event Rate (after selection)



#### JONO Site



## RENO-50 Site



## JUNO MH Sensitivity

PRD 88, 013008 (2013)	w/o $\Delta m^2_{\mu\mu}$	w/ $\Delta m^2_{\mu\mu}$ input (1%)
Statistics only	4σ	5σ
Realistic case	3σ	4σ

#### JUNO MH sensitivity with 6 years' data:

#### Y.F Li *et al,* PRD 88, 013008 (2013)



	Iucal	Core uisu.		Shape	D/S (Stat.)	D/S (Shape)	μμΙ
Size	52.5 km	Real	Real	1%	6.3%	0.4%	1%
$\Delta \chi^2_{MH}$	16	- 3	-1.7	- 1	- 0.6	- 0.1	+ (4-12)

#### Precision Measurements of Oscillation Parameters

JUNO 100k IBD Events A 250 200 200 200 40 40 200 40  $sih^2 2\theta_{13}$ Smeared by 3%/sqrt(E)  $sin^2 2\theta_{12}$ Probing the unitarity of Δm<sup>2</sup><sub>21</sub> U<sub>PMNS</sub> to ~1% more precise than CKM 50 matrix elements ! 2 6 8 4 Eprompt (MeV)

	Statistics	+BG+1% b2b+1% Scale +1% EnonL		
$\sin^2 \theta_{12}$	0.54%	0.67%		
Δm <sup>2</sup> <sub>21</sub>	0.24%	0.59%		
Δm <sup>2</sup> <sub>ee</sub>	0.27%	0.44%		

## Challenges in JUNO

## **\Box** Energy resolution: $3\%/\sqrt{E}$

- > 77% photocathode coverage
- High PDE of PMTs: 35% at QE peak
- Long attenuation length of LS: 20 m (abs. 60m + Rayl. Scatt. 30m)
- **Reactor spectrum** 
  - Direct measurement of the spectrum to 1% by SBL reactor experiments.
  - **Constraint from Daya Bay measurements, 1%.**

	Daya Bay	KamLAND	BOREXINO	JUNO	
LS mass	0.042 kt	1 kt	0.5 kt	20 kt	
<b>Energy Resolution</b>	$7.5\%/\sqrt{E}$	6%/√ <i>E</i>	$5\%/\sqrt{E}$	3%₀/√ <u>E</u>	
Light yield	~160 p.e./MeV	250 p.e./MeV	511 p.e./MeV	1200 p.e./MeV	
Photo-Cathode	120/	2407	2407	770/	
Coverage	~12%	~34%	~34%	////0	

	Paul \$7 (83	JUNO Collaboration	-	JUNO
	enter services in the <u>Marine</u>	a a a a a a a a a a a a a a a a a a a		
Country	Institute		inn	Xiamen University
14	View Physics Leading		1113	NUDT
Relainm	Leinamita libra da Pruvallar		COLUMN C	Charles U.
Brazil	PUC		SA	A DC Dania
Brazil			2	APC Paris
Chile	PCUC		nice	IDUC Strachourg
Chile	BISEE		ince	IFHC Strasbourg
China	Beijing Normal U.		ance	Subatash Nantas
China	CAGS		Ance	Subatech Names
China	ChongQing University		rmany	RWTH Aachen U
China	CIAE		rmany	TUM
China	DGUT		rmany	I Hamburg
China	ECUST	8th JUNO Collaboration Meeting	rmany	BCP FZI Jälich
China	Guangxi U.		citiany	L Mainz
China	Harbin Institute of	Jury 29-20, august and a second	rmany	U Tuchingen
Cinna	Technology		ly	INFN Catania
China	IHEP		de la	INFN di Frascati
China	Jilin U.		ly ly	INFN-Ferrara
China	Jinan U.		de l	INFN-Miland
China	Nanjing U.	A provide the set of the set o	iy he	INEN Milano Disossa
China	Nankai U.		ly he	INFN-Padova
China	NCEPU		iy by	INEN Derugia
China	Pekin U.		ly by	INFN-Perugia
China	Shandong U.		Liston	DINSTECU
China	Shanghai JT U.	Participation of the second seco	KISTAN	INP Massow
China	IMP-CAS	Ru	asia	UND
China	SYSU	Collaboration actablished in July 2015	ssia	MSU
China	Isinghua U.	Collaboration established in July 2015	iwan	National Chiao Tuna U
China	UCAS	Now 66 institutions	iwan	National Taiwan II
Chica	USIC	NOW. OD INSULULIONS	iwan	National United U
China	U. of South China	AAA collaborators	niland	SIT
Chica	Wahan U		Anand	UMDI
Chica	Wear FF U	8 obervers	10%. 1	LMD
China	Aran JI U.	UNCIVEIS UN	123.	UMD2



#### **Given Service Plans**

- Run for 20-30 years
- Likely, double beta decay experiment in 2030

## Searching 0vßß Decays in JUNO



- Budget : \$ 100M for 6 year (Civil engineering: \$ 15M, Detector: \$ 85M)
- **R&D** supported by Samsung (2M\$ for 2015-2017)
- **Efforts on obtaining a full construction fund**
- Schedule
  - > 2016-2021: Facility and detector construction
  - > 2022~ Operation
- Geological survey for design of tunnel and experimental hall
   Cost estimation to be obtained soon

![](_page_20_Picture_8.jpeg)

![](_page_20_Picture_9.jpeg)

### JUNO Detector

![](_page_21_Figure_1.jpeg)

AS: Acrylic sphere; SSLS: stainless steel latticed shell

## Highlights of JUNO Project Progresses

## **Civil Progress**

### **Ground breaking in Jan. 2015**

1020 m slope tunnel excavated out of 1340 m
485 m vertical shaft excavated out of 611 m

![](_page_22_Picture_4.jpeg)

![](_page_22_Picture_5.jpeg)

## Acrylic Sphere R&D

![](_page_23_Picture_1.jpeg)

#### Acrylic divided into 200+ panels

![](_page_23_Picture_3.jpeg)

![](_page_23_Picture_4.jpeg)

![](_page_23_Picture_5.jpeg)

The problems of shrinkage and shape variation were resolved. Three companies had good practices.

![](_page_23_Picture_7.jpeg)

Forming panel size: 3m x 8m x 120mm

![](_page_23_Picture_9.jpeg)

## LS Pilot Plant

- LS requirement \*
  - > **Optical** : >20m A.L @430nm
  - Radio-purity: < 10<sup>-15</sup> g/g (U, Th)
- **Purification** \*\*
  - > Purify 20 ton LAB to test the overall design of purification system at Daya Bay. Plan to replace the target LS in one detector. Al<sub>2</sub>O<sub>3</sub> column pilot plant
- \* **Determine the choice of sub-systems** 
  - Al<sub>2</sub>O<sub>3</sub>, distillation, gas striping, water extraction

Distillation and steam stripping

Installed at **Daya Bay** 

![](_page_24_Picture_10.jpeg)

Steam stripping system

installed in Daya Bay LS hall

![](_page_24_Picture_13.jpeg)

## PMT System

## Finished 20" PMT bidding at the end of 2015:

- -- 15,000 MCP-PMT (NNVT, China)
- -- 5,000 Dynode-PMT (Hamamatsu, Japan)
- **Double calorimetry**
- --~36,000 3" PMT
- -- MELZ(RU), HZC(CH), ETL(UK), Hamamatsu(JP)

![](_page_25_Picture_7.jpeg)

![](_page_25_Picture_8.jpeg)

MCP-PMT

**Dynode-PMT** 

Characteristics	unit MCP-PMT(NNVC)		R12860
Detection Eff.(QE*CE*area)	%	27%, > 24%	27%, > 24%
P/V of SPE		3.5, > 2.8	3, > 2.5
TTS on the top point	ns	~12, < 15	2.7, < 3.5
Rise time/ Fall time	ns	R~2 , F~12	R~5, <7; F~9, <12
Anode Dark Count	Hz	20K, < 30K	10K, < 50K
After Pulse Rate	%	1, <2	10, < 15
		238U:50	238U:400
Radioactivity of glass	ppb	232Th:50	232Th:400
		40K: 20	40K: 40

![](_page_25_Picture_12.jpeg)

## Calibration System

#### **Radioactive sources**

- **G** gamma: <sup>40</sup>K, <sup>54</sup>Mn, <sup>60</sup>Co, <sup>137</sup>Cs
- **D** positrons: <sup>22</sup>Na, <sup>68</sup>Ge
- **D** neutrons: <sup>241</sup>Am-Be, <sup>241</sup>Am-<sup>13</sup>C, <sup>241</sup>Pu-<sup>13</sup>C, <sup>252</sup>Cf

#### Four calibration systems

- **1D:** Automatic Calibration Unit -- ACU
- 2D: Cable Loop System CLS Guide Tube Calibration System -- GTCS
- 3D: Remotely Operated under-liquidscintillator Vehicles -- ROV

![](_page_26_Figure_9.jpeg)

![](_page_26_Figure_10.jpeg)

#### (1) Development of DAQ electronics

Specification for dead time free, high sensitivity and high speed signal processing. Prototype boards to be tested

(2) Develop techniques of LS purification

Reduction of LS radioactivity to 10<sup>-16</sup> g/g of U and Th
 Removal of LS impurities for attenuation length of ~25 m

(3) Mechanical design of detector

Detailed drawing of mechanical parts in progress

(4) Measurement of radioactivity for the detector materials

Evaluate radioactivity of detector parts using HPGe

(5) Measurement device for absolute LS attenuation length

Developed a long pipe device with a laser source and a PMT

- \*  $\theta_{13}$  has been well measured by Daya Bay, RENO and Double Chooz experiments. The ultimate precision will reach ~3%.
- **\*** JUNO and RENO-50 have been designed to determine MH with 3-4  $\sigma$  in 2026 and precisely measure oscillation parameters to < 1%.
- **W** JUNO is a fully funded project and construction/R&D are rapidly progressing.
  - > PMT system, LS, Acrylic sphere, Calibration, readout, ...
  - > Aiming to take data in 2020.
- RENO-50 has R&D funding and various R&D are in progress.
  - > Working for full funding
  - > Aiming to take data in 2022.

**Thanks for your attention!**